



## PCB transformatoren in open uitvoering

type kern	vermogen [VA]	afmetingen w x l x h [mm]	aantal pins No.	Pins r x s [mm]	gewicht [kg]
EI 30/5.5	0.6	30 x 25 x 13.2	10	20 x 5	0.045
EI 30/10.5	1.8	30 x 25 x 19.8	10	20 x 5	0.070
EI 30/12.5	2.3	30 x 25 x 21.8	10	20 x 5	0.080
EI 30/15.5	2.6	30 x 25 x 24.8	10	20 x 5	0.100
EI 30/18.0	3.0	30 x 25 x 27.5	10	20 x 5	0.110
EI 30/23.0	3.2	30 x 25 x 32.0	10	20 x 5	0.135
EI 38/7.5	1.8	38 x 33 x 20,5	10	20 x 5	0.100
EI 38/13.5	4.0	38 x 33 x 26.8	10	20 x 5	0.150
EI 38/16.5	4.5	38 x 33 x 28.8	10	20 x 5	0.250
EI 42/8.5	3.0	42 x 35 x 24.2	12	25 x 5	0.120
EI 42/14.5	5.5	42 x 35 x 30.3	12	25 x 5	0.200
EI 42/20.0	6.5	42 x 35 x 36.0	12	25 x 5	0.250
EI 48/12.5	7	38 x 42 x 28.2	12	27.5 x 5	0.250
EI 48/16.8	10	48 x 42 x 32.6	12	27.5 x 5	0.300
EI 48/20.5	12	48 x 42 x 36.5	12	27.5 x 5	0.350
EI 48/25.5	15	48 x 42 x 41.5	12	27.5 x 5	0.450
EI 54/14.0	12	54 x 45 x 30.7	14	30 x 5	0.350
EI 54/18.8	16	54 x 45 x 35.8	14	30 x 5	0.400
EI 54/23.0	20	54 x 45 x 40.2	14	30 x 5	0.500
EI 54/25.5	22	54 x 45 x 44.4	14	30 x 5	0.550
EI 60/16.0	17	60 x 51 x 37	14	32.5 x 5	0.450
EI 60/21.0	20	60 x 51 x 42	14	32.5 x 5	0.600
EI 60/25.5	28	60 x 51 x 46	14	32.5 x 5	0.700
EI 60/30.5	30	60 x 51 x 51	14	32.5 x 5	0.800
EI 60/35.0	35	60 x 51 x 54	14	32.5 x 5	0.900
EI 66/12.0	17	66x 59 x 34.5	14	35 x 5	0.500
EI 66/18.0	25	66 x 59 x 40.5	14	35 x 5	0.700
EI 66/23.0	33	66 x 59 x 44.5	14	35 x 5	0.800
EI 66/30.0	44	66 x 59 x 51.8	14	35 x 5	0.950
EI 66/34.8	47	66 x 59 x 56	14	35 x 5	1.00
EI 66/40.0	50	66 x 59 x 62.5	14	35 x 5	1.20
EI78/27.5	50	78 x 65 x 54	18	42,5 x 5	1.25
EI78/36.5	60	78 x 65 x 64	18	42,5 x 5	.150
EI78/40.5	70	78 x 65 x 68	18	42,5 x 5	1.70
EI84/29.5	75	84 x 71 x 58	20	45 x 5	1.60
EI84/43.5	100	84 x 71 x 71.5	20	45 x 5	2.10
EI96/35.7	130	96 x 82 x 70	24	57.5 x 5	2.60
EI96/45.5	160	96 x 82 x 80	24	57.5 x 5	3.80
EI96/59.5	200	96 x 82 x 92	24	57.5 x 5	4.60

